

VX1932wm

19" WIDESCREEN LCD

WITH CLEARMOTIV® 2MS
BROADCAST-QUALITY VIDEO

The ultimate 2ms gaming display.

ViewSonic's 19" VX1932wm widescreen LCD is the ultimate gaming LCD with ultra-fast 2ms video response for unparalleled GAMING, ENTERTAINMENT OR GRAPHICS-INTENSIVE APPLICATIONS. Amplified Impulse™ technology delivers broadcast-quality, fast-action video so your games, movies and DVDs are amazingly clear. The widescreen enhances your entertainment and increases productivity. View two documents side by side or work in two applications without toggling. Connect your game console, DVD player and other components through the DIGITAL (DVI-D) AND ANALOG INPUTS. Enjoy a full multimedia entertainment experience with INTEGRATED STEREO SPEAKERS. A Kensington® security port provides theft deterrence and the OSD and power lock prevent unauthorized changes to your optimal screen settings. The VX1932wm's glossy piano-black finish beautifully complements any desktop.

AMAZING GAMES AND HD CONTENT

- > Full 19" viewable widescreen with 1440x900 resolution
- > ClearMotiv® 2ms video response time
Ultra-fast 2ms video response enables digital HD broadcast-quality video.
- > 2000:1 dynamic contrast ratio
- > Stylish slim-bezel design with glossy, piano-black finish
The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > OptiSync® digital/analog inputs expand your connectivity
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > Multimedia enhanced
Save desk and workspace and enjoy rich, stereo sound with built-in stereo speakers.
- > OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows Vista approved
- > PC and Mac® compatible
- > MPR II and ENERGY STAR® qualified



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic®
See the difference® 

VX1932wm

19" WIDESCREEN LCD WITH CLEARMOTIV® 2MS BROADCAST-QUALITY VIDEO



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14173-00B-09/08] VX1932wm-3

LCD	Type	19" Wide Color TFT Active Matrix LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	700:1 (typ), 2000:1 (DCR)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	2ms gray-to-gray (typ)
		5ms black-white-black (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (TMDS, 100 ohms)
	Frequency	F _H : 30~82kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1440x900 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1440x900
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2x2-watt
POWER	Voltage	AC 100~240V, 50~60Hz (auto switch)
	Consumption	35W (typ)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING	Temperature	32~104°F (0~40°C)
CONDITIONS	Humidity	20~80% (non-condensing)
DIMENSIONS	Physical with stand	17.7" x 17" x 8.2" (450mm x 434mm x 209mm)
	Physical without stand	17.7" x 13.4" x 2.8" (450mm x 341mm x 65.5mm)
WEIGHT	Net with stand	11.5 lb. (5.2 kg)
	Net without stand	10.4 lb. (4.7 kg)
	Gross with stand	14.8 lb. (6.7 kg)
REGULATIONS	UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS (covers GS), ERGO (ISO13406-2 & MPR II), MPR II, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS	
RECYCLE/DISPOSAL	The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	
POWER MANAGEMENT	Meets MPR II and ENERGY STAR® standards	
PACKAGE CONTENTS	LCD display, power cable, 15-pin VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD	
WARRANTY	Three-year limited warranty on LCD, parts and labor.	

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com